



## SPECIFICATIONS

A pair of solid brass door handles with 10mm sprung rose.

Compatible with 45mm and 60mm backset tubular latches and 45mm or 60mm mortice locks.

Fits door thickness of 32mm minimum to 40mm maximum with standard fixings | extended fixings available on request.

## FINISHES

- Satin Brass Unlacquered
- Satin Brass Enameled
- Polished Brass Unlacquered
- Light Antique Bronze Unlacquered
- Light Antique Bronze Enameled
- Medium Antique Bronze Unlacquered
- Medium Antique Bronze Enameled
- Dark Antique Bronze Unlacquered
- Dark Antique Bronze Enameled
- Satin Nickel
- Satin Black Powdercoated
- Satin White Powdercoated

## PARTS

- 1x pair of sprung door levers
- 2x Smart Screws 38-40mm Door thickness
- 2x Smart Screws 34-38mm Door thickness
- 2x Smart Screws 32-34mm Door thickness
- 2x Smart Screw Extension adaptors
- 2x sprung-half spindles
- 1x allen key

## CARE INSTRUCTIONS

Only use a damp cloth with diluted mild detergent to remove any stains or finger prints. Residue build-up may cause corrosion or discolouration of the original finish.

Caring for lacquered or powder-coated items is much like caring for painted items. Wipe the product with a damp cloth, with diluted soap.

Dry the products thoroughly with a clean soft cloth.



# BLAS

innovation. performance. design.